



SPB Aerosol Adhesive 500ml

Product Data Sheet –
523000.CB

Issue 2
Date 02/2018

Features and Benefits

- Spray applied high-strength adhesive that allows quick bonding. Cleaner, simpler application
- Up to 6 times faster application than traditional Bonding Adhesive
- Up to 4 times faster drying than traditional Bonding Adhesive
- Far greater operational window than traditional Bonding Adhesive
- More accurate application
- Zero wastage.
- Up to 3m² fully bonded per aerosol can



ClassicBond SPB Aerosol Bonding Adhesive can dramatically reduce the overall time spent both on application & waiting for flash off, resulting in jobs being completed without the elements interfering.

SPB Aerosol Adhesive is a high-strength adhesive, specially formulated for spray application, for bonding of non-backed EPDM membranes to a variety of substrates

Intended Uses

ClassicBond Aerosol Adhesive is designed as an alternative to brushable Bonding Adhesive. It will bond to a variety of substrates & provides unrivalled bond strength

Application

When ready to use:

1. The surface, on or against which adhesive is to be applied, shall be clean, smooth, dry, and free of fins, sharp edges, loose and foreign materials, oil and grease.
2. Hold aerosol can 100-150mm from surface to be coated and depress.
3. Once adhesive has been applied to both surfaces allow adhesive to become dry to the touch.
4. Mate the two surfaces together avoiding wrinkles and apply pressure with roller to the membrane to consolidate the bond.

Precautions

1. SPB Adhesive is **EXTREMELY FLAMMABLE**
- It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Store and use away from all sources of heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapours are heavier than air and may travel along ground to a distant ignition source and flash back. A red caution label is required when shipping.
2. Harmful by inhalation. Inhalation may cause nausea & vomiting. May cause dizziness & headache. Move exposed person to fresh air. Seek medical attention.



SPB Aerosol Adhesive 500ml

Features and Benefits

- Spray applied high-strength adhesive that allows quick bonding. Cleaner, simpler application
- Up to 6 times faster application than traditional Bonding Adhesive
- Up to 4 times faster drying than traditional Bonding Adhesive
- Far greater operational window than traditional Bonding Adhesive
- More accurate application
- Zero wastage.
- Up to 3m² fully bonded per canister

3. Harmful if swallowed. Ingestion may cause nausea & vomiting. Ingestion is irritating to the respiratory tract & may cause damage to the central nervous system.

DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately & show container or label.

4. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of clean water for at least 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

5. May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap & water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

6. Job site storage temperatures in excess of 32°C (90°F) may affect product shelf life. Should the Bonding Adhesive be stored at temperatures below 15°C (60°F), restore to room temperature prior to use.

7. Coverage rates are average and may vary due to conditions on the job site.

8. **KEEP OUT OF THE REACH OF CHILDREN.**

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The product labels
2. ClassicBond SPB Safety Data Sheet

ClassicBond SPB Adhesive	
Typical Properties & Characteristics*	
Colour	Green
Description	Aqueous Solution
Flash Point	-41° C
Packaging	500ml Aerosol
Coverage	Up to 3m ² per canister
Shelf Life	1 year

Exclusive British Isles Distributors for Carlisle-SynTec and ClassicBond EPDM single ply roofing materials.

Flex-R Ltd, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433 www.classicbond.co.uk